

Technical Data Sheet


Temper Proof Pull Tight Security Seal: -

- A. Material: Poly Propylene Copolymer (PPCP) Grade (Superior quality)
- B. Color: Single
- C. Tail Length: 300mm \pm 10mm /strip.
- D. Tail Breadth: 6mm (minimum)
- E. Flap Size: 70mm X 30mm (approx.)
- F. Total length=370mm \pm 10mm.
- G. Lock Mechanism: SS metal insert with irreversible Mechanism.
- H. Identification on each seal with PSPCL logo and serial no. (Laser Marking).
- I. Packing: Seals should be packed in serial order of seal number.
- J. Tensile Strength: 40 kg

Note:

- 1. For technical suitability of material, each firm will Supply 10 no samples of seal along with the offer.
- 2. Firm will Provide Material Certificate of the seals along with the offer, if any discrepancy found at later stage, it will be in firm's account.
- 3. Before manufacturing seals, L-1 firm will get approve PSPCL logo and serial no. to be printed on the seals from ASE/Coal & Environment, Chemical Department, GHTP, Lehra Mohabbat.

vetted please
w/z
04-7-25


ASE/ Coal & Environment
Chemical Department,
GHTP, Lehra Mohabbat

vetted please


ASE / Coal & Env.,
Chemical Department,
GHTP, Lehra Mohabbat.